Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No.

59 739 - 13 HH

Company

Gustav Klauke GmbH Auf dem Knapp 46

42855 Remscheid, GERMANY

Product Description

Pressure terminal connectors

Type

"R" series lugs and connectors
"L" series lugs and connectors

Environmental Category

A+H

Technical Data / Range of Application

Cross section: 1,.5mm². up to 400mm² respective 630mm² (L-series)

Basic material: copper (Cu-HCP)

Voltage:

depending on lug type and application up to 36 kV

The use of the correct crimping and cutting tools of the manufacturer is mandatory.

The screw connection has to be carried out the correct torque.

Application:

Cable lugs for installation inside switchboard/enclosures onboards ships and fixed / mobile offshore installations.

Test Standard

GL Guidelines for the Performance of Type Approvals Chapter 2, Edition 2012

IEC 61238-1:2003/2004; DIN EN 61373:1999; EN 61400-1:2011

Documents

RWE test reports 07 157-2L:2012; 07 157-2R:2012; 07 157-10:2012;

Brunel reports P12-9580: 2012; P06-0731:2008

Klauke catalogue 2012/2013

Remarks

Operation instruction of the manufacturer has to be observed. Actual cable cross

section has to be considered for the selection of cable lugs.

Valid until

2018-01-15

Page

1 of 3

100

File No. 1.0.04

Hamburg, 2013-01-16

Type Approval Symbol



Germanischer Lloyd

Arne Schaarmann

Joachim Zipfel

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No.

59 739 - 13 HH

The following terminal connestors "R" Series are coverd by this certificate:

- 1.) Straight, Cat. Nos. 91R, 92R, 93R, 94R, 95R followed by a 1-digit number, may be followed by Suffix bk.
- 2.) Straight, Cat. Nos. 1R, 2R, 3R, 4R, 5R, 6R, 7R, 8R, 9R, 10R, 11R, 12R, 13R, or 14R, followed by /1 or 2-digit number, may be followed by Suffix MS and/or by Suffix bk, Ni, Pb.
- 3.) Angled-45 degree, Cat. Nos. 41R, 42R, 43R, 44R, 45R, 46R, 47R, 48R, 49R, 50R, 51R, 52R, 53R, or 54R, followed by a /1 or /2-digit number, by Suffix -45, may be followed by Suffix MS and/or by Suffix bk, Ni, Pb.
- 4.) Angled-90 degree, Cat. Nos. 41R, 42R, 43R, 44R, 45R, 46R, 47R, 48R, 49R, 50R, 51R, 52R, 53R or 54R, followed by a /1 or /2- digit number, may be followed by Suffix MS and/or by Suffix bk, Ni, Pb.
- 5.) Narrow Palm Type, Cat. Nos. 5SG, 6SG, 7SG, 8SG, 9SG, 10SG, 11SG, 12SG, or 13SG, followed by 1 or 2-digit number, may be followed by Suffix bk, Ni.
- 6.) Fork Type, Cat. Nos. 91C, 92C, 93C, 94C, 95C, 96C, or 97C, followed by a 1-digit number, may be followed by Suffix bk.
- 7.) Butt-Type, Cat. Nos. 17R, 18R, 19R, 20R, 21R, 22R, 23R, 24R, 25R, 26R, 27R, 28R, 29R, 30R, 31R, 32R, 33R, or 34R, may be followed by Suffix bk, Ni.
- 8.) Cross-Connectors, Type KV1.5, KV2.5, KV4, KV6, KV10, KV16, KV25, KV35, KV50, KV70, KV95, KV120, KV150, KV185, or KV240, may be followed by Suffix bk, Ni, Pb.
- 9.) T-Connectors, Type TV1.5, TV2.5, TV4, TV6, TV10, TV16, TV25, TV35, TV50, TV70, TV95, TV120, TV150, TV185, or TV240, may be followed by Suffix bk, Ni, Pb

Valid until

2018-01-15

Page

2 of 3

File No.

1.0.04

Hamburg, 2013-01-16

Type Approval Symbol



Germanischer Lloyd

Arne Schaarmann

Joachim Zipfel

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No.

59 739 - 13 HH

The following terminal connectors "L" series are coverd by this certificate

- 1.) Straight, Cat. Nos. L0.75, L1.5, L2.5, L4, L6, L10, L16, L25, L35, L50, L70, L95, L120, L150, L185, L240, L300, L400, L500 or L630, followed by a 1 or 2-digit number, and by Suffix MS, may be followed by Suffix bk.
- 2.) Angled-45 degree, Cat. Nos. L6, L10, L16, L25, L35, L50, L70, L95, L120, L150, L185, L240, L300, L400, followed by a /1 or /2- digit number, and by Suffix -45, may be followed by Suffix bk.
- 3.) Angled-90 degree, Cat. Nos. L6, L10, L16, L25, L35, L50, L70, L95, L120, L150, L185, L240, L300, L400, followed by a /1 or /2- digit number, and by Suffix -90, may be followed by Suffix bk.
- 4.) Pressure cable connectors, "L" Series, Butt-Type, Cat. Nos. LV0.75, LV1.5, LV2.5, LV4, LV6, LV10, LV16, LV25, LV35, LV50, LV70, LV79, LV120, LV150, LV185, LV240, LV300, LV400, LV500, or LV630, may be followed by Suffix bk.
- 5.) Cross-connectors, Type KVL1.5, KVL2.5, KVL4, KVL6, KVL10, KVL16, KVL25, KVL35, KVL50, KVL70, KVL95, KVL120, KVL150, KVL185, or KVL240, may be followed by Suffix bk.
- 6.) T-Connectors, Type TVL1.5, TVL2.5, TVL4, TVL6, TVL10, TVL16, TVL25, TVL35, TVL50, TVL70, TVL95, TVL120, TVL150, TVL185, or TVL240, may be followed by Suffix bk

Valid until

2018-01-15

Page

3 of 3

File No.

1.0.04

Hamburg, 2013-01-16

Type Approval Symbol



Germanischer Lloyd

Arne Schaarmann

Joachim Zipfel

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".